

## FERTIG OAK POMPEIUS | Collection Antique



### INSTALLATION METHODS

|                            |     |
|----------------------------|-----|
| Floating Installation      | YES |
| Click System               | YES |
| All - Over Glueing         | YES |
| Suitable For Heated Floors | YES |

### GRADING CRITERIA

Knotty grading with slightly sapwood mix-grade royal

### PRODUCT DETAILS

Collection Antique

|               |                        |                             |                         |
|---------------|------------------------|-----------------------------|-------------------------|
| Product Range | Plank                  | Top Layer                   | 4 mm                    |
| Construction  | 3 Layered Engineered   | Thickness                   | 15 mm                   |
| Specie        | Eupean Oak             | Width                       | 260 mm                  |
| Pattern       | 1- Strip               | Length                      | 2200 mm                 |
| Process       | Brushed                | Pack Size                   | 3,432 m2                |
| Finish        | White Oiled            | Grade                       | Heavy Rustic            |
| Profile       | Click System           | Thermal Conductivity        | 0,14 m <sup>2</sup> K/W |
| Edge Profile  | 4v Sided Bevelled Edge | Thermal Transmittance Value | 0,12 m <sup>2</sup> K/W |



- \* Please note that this is a smoked/ tumbled product. This reactive process will typically generate a wide range of colour variation in the product
- \* This technical data sheet was written by Fertig & Holz. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.